DESSO Textile floor covering - Broadloom

Axminster Sculpt

Preliminary specification according to EN 1307

Type of manufacture	ISO 2424		Woven - Axminster					
Aspect	ISO 2424		Structured cut pile					
Dye method			Hank dyed					
Width		cm	400		ft	13.1		
Primary backing	ISO 2424		Polypropylene weft / Polyester-based warp					
Secondary backing	ISO 2424		Copolymer					
Pile fibre composition	ISO 2424		80% wool - 20% polyamide					
Total thickness	ISO 1765	mm	9.5		inch	0.4		
Effective pile thickness	ISO 1766	mm	7.0		inch	0.28		
Total mass	ISO 8543	g/m²	1860		oz/yd²	54.9		
Total pile mass	ISO 2424	g/m²	1490		oz/yd²	44.0		
Effective pile mass	ISO 8543	g/m²	1040		oz/yd²	30.7		
Pile density	ISO 8543	g/cm³	0.149		lb/in³	0.0054		
Number of tufts	ISO 1763	/dm²	975		/yd²	81520		
Stroll test	ISO 6356	kV	-					
Vertical resistance	ISO 10965	Ohm	-					
Horizontal resistance	ISO 10965	Ohm	-					
Use classification	EN 1307		33 Commercial - heavy use					
Luxury rating	EN 1307		LC 4					
Impact sound reduction ΔL_w	ISO 10140	dB	31					
Sound absorption	ISO 354	Freq. Hz	125	250	500	1000	2000	4000
		α_s	0.01	0.06	0.13	0.27	0.49	0.64
Noise reduction	ISO 354	α_w	0.25					
Thermal resistance	ISO 8302	m².K/W	0.154					
Flammability	EN 13501-1		Cfl - s1 (glued tested)					
Prodis - GUT	www.pro-dis.info		-					

CE
EN 14041
0493-CPR-0106

Manufactured by:
Tarkett NV
Robert Ramlotstraat 89
B - 9200 Dendermonde

Cfl-s1 DS

Quality- and Environmental Management System Certification ISO 9001 & ISO 14001

Tarkett's flooring products are to be installed in full accordance with DESSO installation instructions and recognized trade standards. An effective, regular cleaning and maintenance program is vital for retaining a high appearance level. Tarkett's flooring products should only be used as floorcoverings. Note: Tarkett reserves the right to change this specification without prior notice; changes are subject to normal production tolerances. For the latest versions of the technical specifications, visit www.tarkett.com

EN-20200205

Tarkett BV
Taxandriaweg 15
NL-5142 PA Waalwijk

Tarkett